



400 series Built-in oven, Door Hinge: left

BO451112

- Handleless door / automatic door opening
- Pyrolytic system
- 13 heating methods with core temperature probe and baking stone function
- Automatic programmes
- Core temperature probe with estimation of cooking time
- TFT touch display
- Panel-free appliance with surface control module
- Electronic temperature control from 30 °C to 300 °C
- Net volume 76 litres

Heating methods

- Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

- Automatic door opening.

- Rotary knob and TFT touch display operation.
- Clear text display.
- Option to save individual recipes (incl. core temperature probe).
- Personalisation of automatic programmes.
- Information key with use indicators.
- Side-opening door opens up to 180° angle.

Features

- Three-point core temperature probe with automatic shut-off and estimation of cooking time.
- Automatic programmes.
- Baking stone socket.
- Actual temperature display.
- Rapid heating.
- Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
- 60 W halogen light on the top.
- 10 W halogen light on the side.
- Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.
- Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
- The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country.

For further information please check: home-connect.com.

Safety

- Thermally insulated door with quadruple glazing.
- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

Cleaning

- Pyrolytic system.
- Gaggenau enamel.
- Heated catalyser to clean the oven air.

Planning notes

- Door hinge not reversible.
- The facade of the appliance extends 47 mm from the furniture cavity.
- Consider the overhang when planning to open drawers next to the appliance.
- When planning a corner solution, pay attention to the 90° door opening angle.
- To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.
- The mains socket needs to be planned outside the built-in niche.
- The LAN port can be found at the back on the upper right side.



Connection

- Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
- Total connected load 3.7 KW.
- Plan a connection cable.
- Plan a LAN cable.
- Power consumption standby/display on 0.7 W.
- Power consumption standby/display off 0.5 W.
- Power consumption standby/network 1.4 W.
- Time auto-standby/display on 20 min.
- Time auto-standby/display off 20 min.
- Time auto-standby/network 20 min.
- Please check the user manual for how to switch off the WiFi module.

The difference is GAGGENAU