



400 series Vario wine cooler with glass door, 212.5 x 60.3 cm

RW466364

- 3 independently controllable climate zones
- Consistent temperatures with exact control from +5 °C to +20 °C
- Humidity control
- Stainless steel interior
- Fully extendable bottle trays in oak wood and solid aluminium in anthracite
- Bottle trays with hidden telescopic rails
- Warm white and glare-free LED light spots
- 5 preset lighting scenarios, selectable via TFT display
- Opening assist for door with two options:
 1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
- Low-vibration operation
- TFT touch display
- Capacity 99 bottles

Handling

- TFT touch display operation.
- Clear text display.

Technical Features

- Dynamic cold air distribution.
- Automatic defrosting with defrost water evaporation.
- Cushioned door closing system.
- Activated charcoal air filter.
- UV-protection.
- Rest mode certified by Star-K.
- When rest mode is active, the appliance can only be opened using a handle.
- Open-door and malfunction alarm.
- Home network integration for digital services (Home Connect) wireless via WiFi.
- The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Features

- Capacity 99 bottles (based on 0.75/l standard bottles).
- 12 bottle trays, - 9 fully extendable trays - 3 suitable for storage of Magnum bottles.
- Flexible interior configuration possible by adding or removing fully extendable bottle trays.
- Storage of up to 12 Magnum bottles with standard tray configuration (12 bottle trays).

- Space for max. 12 bottle trays.
- 2 brilliant LED light spots with warm white, glare-free light in each climate zone.
- 5 different lighting scenarios can be selected for individual wine presentation.
- Net volume 361 litres.

Consumption data

- Energy efficiency class A at a range of energy efficiency classes from A+++ to G.
- Energy consumption 171 kWh/year.
- Noise level 42 dB (re 1 pW).

Planning notes

- Flat hinge.
- Door hinge right, reversible.
- Door opening angle of 115°, fixable at 90°.
- Max. door panel weight 73 kg.
- The mains socket needs to be planned outside the built-in niche.
- No transport/operation above 2000 m sea level.

Connection

- Total connected load 0.300 KW.
- Connecting cable 3.0 m, pluggable.